

14 MM CLASSIC - LIGURIA A16105



- ·		- 1	
1)ım	ension	nla	ank

LENGTH	82-1/2" RL (2100 mm RL)
WIDTH	9 1/2" (240 mm)
TOTAL THICKNESS	9/16" (14 mm)

Dimer	nsion	hox

BOX LENGTH	82 3/4" (2100 mm)
BOX WIDTH	9 4/5" (250 mm)
BOX THICKNESS	2 1/2"(60 mm)
BOX WEIGHT	46 lb
LAYERS/BOX	4
SQFT/BOX	21.74 saft

Dimension pallet

PALLET LENGTH	86 2/3" (2200 mm)
PALLET WIDTH	39 1/2" (1000 mm)
PALLET HEIGHT	45 1/4" (1150 mm)
PALLET WEIGHT	2811 lb
BOX/PALLET	60
SQFT/PALLET	1304.40 sqft

FEATURES

Top layer

WOOD TYPE	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC
CONSTRUCTION	2-layer
BEVEL	Micro bevel 4 sides (0.5 mm)
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Engineered
BASE OF THE SUPPORT	Plywood

Placement

SYSTEM

Tongue and groove

APPLICATIONS

- · Light household use
- · Moderate commercial use
- Normal commercial use
- · Normal household use
- · Intensive commercial use

UNDERFLOOR HEATING

Yes

RE-SANDABLE

Yes

[©] This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables, graphs should in no way be distributed, used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables, graphs used in this sheet are intended only as illustrations. No rights can be derived from them.



14 MM CLASSIC - LIGURIA A16105

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION









