



### Dimension plank

<b>LENGTH</b>	92 1/2" RL ( 2350 mm RL)
<b>WIDTH</b>	7 1/2" (192 mm)
<b>TOTAL THICKNESS</b>	5/8" (15 mm)

### Dimension box

<b>BOX LENGTH</b>	93" (2362 mm)
<b>BOX WIDTH</b>	7 2/3" (195 mm)
<b>BOX THICKNESS</b>	2 1/2" (64 mm)
<b>BOX WEIGHT</b>	45 lb
<b>LAYERS/BOX</b>	4
<b>SQFT/BOX</b>	19.42 sqft

### Dimension pallet

<b>PALLET LENGTH</b>	93 2/3" (2380 mm)
<b>PALLET WIDTH</b>	38 1/2" (980 mm)
<b>PALLET HEIGHT</b>	41 1/2" (1055 mm)
<b>PALLET WEIGHT</b>	3375 lb
<b>BOX/PALLET</b>	75
<b>SQFT/PALLET</b>	1456.50 sqft

## FEATURES

### Top layer

<b>WOOD TYPE</b>	Oak
<b>LATIN NAME</b>	Quercus Robur
<b>GRADE</b>	CLASSIC
<b>CONSTRUCTION</b>	2-layer
<b>BEVEL</b>	Micro bevel 2 long sides (0,5 mm)
<b>SURFACE STRUCTURE</b>	Brushed

### Composition of the support

<b>SUPPORT TYPE</b>	Engineered
<b>BASE OF THE SUPPORT</b>	Plywood

### Placement

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	<ul style="list-style-type: none"> <li>· Light household use</li> <li>· Moderate commercial use</li> <li>· Normal commercial use</li> <li>· Normal household use</li> <li>· Intensive commercial use</li> </ul>	Yes
		<b>RE-SANDABLE</b>
		Yes

## TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m <sup>2</sup> k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

## CERTIFICATION



EN 14342

