# 15 MM CLASSIC - NERO
**A210346**




### Dimension plank

| | |
|---|---|
| **LENGTH** | 92 1/2″ (2350 mm RL) |
| **WIDTH** | 7 1/2″ (192 mm) |
| **TOTAL THICKNESS** | 5/8″ (15 mm) |

### Dimension box

| | |
|---|---|
| **BOX LENGTH** | 93″ (2362 mm) |
| **BOX WIDTH** | 9 3/4″ (248 mm) |
| **BOX THICKNESS** | 2 1/2″ (64 mm) |
| **BOX WEIGHT** | 45 lb |
| **LAGEN/PAK** | 4 |
| **SQFT/BOX** | 24.48 sqft |

### Dimension pallet

| | |
|---|---|
| **PALLET LENGTH** | 93 2/3″ (2380 mm) |
| **PALLET WIDTH** | 38 1/2″ (980 mm) |
| **PALLET HEIGHT** | 41 1/2″ (1055 mm) |
| **GEWICHT PALLET** | 3375 lb |
| **BOX/PALLET** | 75 |
| **SQFT/PALLET** | 1836.00 sqft |

## FEATURES

### Top layer

| | |
|---|---|
| **HOUTSOORT** | Oak |
| **LATIJNSE NAAM** | Quercus Robur |
| **SORTERING** | CLASSIC |
| **OPBOUW** | 2-layer |
| **VELLING** | Micro bevel 2 long sides (0,5 mm) |
| **OPPERVLAKTESTRUCTUUR** | Brushed |

### Composition of the support

| | |
|---|---|
| **SUPPORT TYPE** | Engineered |
| **BASE OF THE SUPPORT** | Plywood |

### Placement

**SYSTEM**

Tongue and groove

**APPLICATIONS**

- Light household use
- Moderate commercial use
- Normal commercial use
- Normal household use
- Intensive commercial use

**VLOERVERWARMING**

Yes

**HERSCHUURBAAR**

Yes

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.

# 15 MM CLASSIC - NERO
**A210346**

## TECHNICAL SPECIFICATIONS

| | Norm | Result |
|---|---|---|
| **REACTION TO FIRE** | EN 13501-1 | Dfl-S1 |
| **FORMALDEHYDE EMISSION** | CARB PH2 | CARB PH2 |
| **PCP** | CEN/TR 14823 | ≤ 5ppm |
| **THERMAL CONDUCTIVITY** | EN 12667 / ISO 8302 | 0,11m² k/w |
| **BIOLOGICAL DURABILITY** | EN 335 | Class 1 |
| **BREAKING STRENGTH** | EN 1533 | Pass |
| **SLIPPERINESS** | EN 15676 | Pass |
| **MOISTURE CONTENT** | EN 13183-1 | 7% (+/-2%) |

## CERTIFICATION

EN 14342

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.