



## Dimension plank

<b>LENGTH</b>	86 1/2" RL (2200 mm RL)
<b>WIDTH</b>	7" (180 mm)
<b>TOTAL THICKNESS</b>	9/16" (14 mm)

## Dimension box

<b>BOX LENGTH</b>	87" (2210 mm)
<b>BOX WIDTH</b>	7 1/2" (190 mm)
<b>BOX THICKNESS</b>	3 2/6" (85 mm)
<b>BOX WEIGHT</b>	40 lb
<b>LAYERS/BOX</b>	6
<b>SQFT/BOX</b>	25.62 sqft

## Dimension pallet

<b>PALLET LENGTH</b>	87 4/5" (2230 mm)
<b>PALLET WIDTH</b>	47 1/4" (1200 mm)
<b>PALLET HEIGHT</b>	43 2/3" (1100 mm)
<b>PALLET WEIGHT</b>	2414 lb
<b>BOX/PALLET</b>	60
<b>SQFT/PALLET</b>	1537.20 sqft

## FEATURES

## Top layer

<b>WOOD TYPE</b>	Oak
<b>LATIN NAME</b>	Quercus Robur
<b>GRADE</b>	AB
<b>CONSTRUCTION</b>	2-layer
<b>BEVEL</b>	Micro bevel 2 long sides (0,5 mm)
<b>SURFACE STRUCTURE</b>	Smooth

## Composition of the support

<b>SUPPORT TYPE</b>	Engineered
<b>BASE OF THE SUPPORT</b>	Plywood

## Placement

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	<ul style="list-style-type: none"><li>· Light household use</li><li>· Moderate commercial use</li><li>· Normal commercial use</li><li>· Normal household use</li><li>· Intensive commercial use</li></ul>	Yes
		<b>RE-SANDABLE</b>
		Yes

### TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m <sup>2</sup> k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

### CERTIFICATION



EN 14342

