



Dimension plank

LENGTH	82-1/2" RL (2100 mm RL)
WIDTH	9 1/2" (240 mm)
TOTAL THICKNESS	9/16" (14 mm)

Dimension box

BOX LENGTH	82 3/4" (2100 mm)
BOX WIDTH	9 4/5" (250 mm)
BOX THICKNESS	2 1/2" (60 mm)
BOX WEIGHT	46 lb
LAYERS/BOX	4
SQFT/BOX	21.74 sqft

Dimension pallet

PALLET LENGTH	86 2/3" (2200 mm)
PALLET WIDTH	39 1/2" (1000 mm)
PALLET HEIGHT	45 1/4" (1150 mm)
PALLET WEIGHT	2810 lb
BOX/PALLET	60
SQFT/PALLET	1304.40 sqft

FEATURES

Top layer

WOOD TYPE	Oak
LATIN NAME	Quercus Robur
GRADE	PRIME
CONSTRUCTION	2-layer
BEVEL	Micro bevel 4 sides (0.5 mm)
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Engineered
BASE OF THE SUPPORT	Plywood

Placement

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	<ul style="list-style-type: none">· Light household use· Moderate commercial use· Normal commercial use· Normal household use· Intensive commercial use	Yes
		RE-SANDABLE
		Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	CARB PH2	CARB PH2
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

