

15 MM CLASSIC - CAMILIA A16310



C ·				
I)ım	ension	n	lan	k

LENGTH	94-1/2" (2400 mm RL)
WIDTH	7" (180 mm)
TOTAL THICKNESS	5/8" (15 mm)

Dimension box	
BOX LENGTH	96-1/2" (2450 mm)
BOX WIDTH	7-1/2" (185 mm)
BOX THICKNESS	3-2/3" (90 mm)
BOX WEIGHT	46 lb
LAYERS/BOX	6
SQFT/BOX	27.88 sqft

Dimension pallet	
PALLET LENGTH	96-1/2" (2450 mm)
PALLET WIDTH	45-1/2" (1150 mm)
PALLET HEIGHT	34-2/3" (880 mm)
PALLET WEIGHT	2248 lb
BOX/PALLET	48
SQFT/PALLET	1338.17 saft

FEATURES

Top layer

WOOD TYPE	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC
CONSTRUCTION	3-layer
BEVEL	Micro bevel 4 sides (0.5 mm)
SURFACE STRUCTURE	Brushed

Composition of the support

SUPPORT TYPE	Fir
BASE OF THE SUPPORT	Fir

Placement

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use	Yes
	· Moderate commercial use	RE-SANDABLE
		Yes
	Normal commercial use	
	Normal household use	
	· Intensive commercial use	

[©] This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables, graphs should in no way be distributed, used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables, graphs used in this sheet are intended only as illustrations. No rights can be derived from them.



15 MM CLASSIC - CAMILIA A16310

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	CARB PH2	CARB PH2
PCP	CEN/TR 14823	≤5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION









