



© Lalegno

## Dimension plank

<b>LENGTH</b>	94-1/2" (2400 mm RL)
<b>WIDTH</b>	7" (180 mm)
<b>TOTAL THICKNESS</b>	5/8" (15 mm)

## Dimension box

<b>BOX LENGTH</b>	96-1/2" (2450 mm)
<b>BOX WIDTH</b>	7-1/2" (185 mm)
<b>BOX THICKNESS</b>	3-2/3" (90 mm)
<b>BOX WEIGHT</b>	46 lb
<b>LAYERS/BOX</b>	6
<b>SQFT/BOX</b>	27.88 sqft

## Dimension pallet

<b>PALLET LENGTH</b>	96-1/2" (2450 mm)
<b>PALLET WIDTH</b>	45-1/2" (1150 mm)
<b>PALLET HEIGHT</b>	34-2/3" (880 mm)
<b>PALLET WEIGHT</b>	2248 lb
<b>BOX/PALLET</b>	48
<b>SQFT/PALLET</b>	1338.17 sqft

**FEATURES**

## Top layer

<b>WOOD TYPE</b>	Oak
<b>LATIN NAME</b>	Quercus Robur
<b>GRADE</b>	CLASSIC
<b>CONSTRUCTION</b>	3-layer
<b>BEVEL</b>	Micro bevel 4 sides (0.5 mm)
<b>SURFACE STRUCTURE</b>	Brushed

## Composition of the support

<b>SUPPORT TYPE</b>	Fir
<b>BASE OF THE SUPPORT</b>	Fir

## Placement

<b>SYSTEM</b>	<b>APPLICATIONS</b>	<b>UNDERFLOOR HEATING</b>
Tongue and groove	<ul style="list-style-type: none"><li>· Light household use</li><li>· Moderate commercial use</li><li>· Normal commercial use</li><li>· Normal household use</li><li>· Intensive commercial use</li></ul>	Yes
		<b>RE-SANDABLE</b>
		Yes

**TECHNICAL SPECIFICATIONS**

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m <sup>2</sup> k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

**CERTIFICATION**



EN 14342

