



Dimension plank

| | |
|------------------------|------------------|
| LENGTH | 18-1/5" (460 mm) |
| WIDTH | 4-3/4" (120 mm) |
| TOTAL THICKNESS | 9/16" (14 mm) |

Dimension box

| | |
|----------------------|------------------|
| BOX LENGTH | 32-1/3" (820 mm) |
| BOX WIDTH | 11" (280 mm) |
| BOX THICKNESS | 7" (180 mm) |
| BOX WEIGHT | 57 lb |
| LAYERS/BOX | 24 |
| SQFT/BOX | 23.20 sqft |

Dimension pallet

| | |
|----------------------|-------------------|
| PALLET LENGTH | 39-1/3" (1000 mm) |
| PALLET WIDTH | 47-1/4" (1200 mm) |
| PALLET HEIGHT | 41-1/3" (1050 mm) |
| PALLET WEIGHT | 1456 lb |
| BOX/PALLET | 25 |
| SQFT/PALLET | 579.85 sqft |

FEATURES

Top layer

| | |
|--------------------------|------------------------------|
| WOOD TYPE | Oak |
| LATIN NAME | Quercus Robur |
| GRADE | PRIME |
| CONSTRUCTION | 3-layer |
| BEVEL | Micro bevel 4 sides (0.5 mm) |
| SURFACE STRUCTURE | Brushed |

Composition of the support

| | |
|----------------------------|------------|
| SUPPORT TYPE | Engineered |
| BASE OF THE SUPPORT | Plywood |

Placement

| SYSTEM | APPLICATIONS | UNDERFLOOR HEATING |
|-------------------|----------------------------|--------------------|
| Tongue and groove | · Light household use | Yes |
| | · Moderate commercial use | RE-SANDABLE |
| | · Normal commercial use | Yes |
| | · Normal household use | |
| | · Intensive commercial use | |

TECHNICAL SPECIFICATIONS

| | Norm | Result |
|-----------------------|---------------------|------------------------|
| REACTION TO FIRE | EN 13501-1 | Dfl-S1 |
| FORMALDEHYDE EMISSION | CARB PH2 | CARB PH2 |
| PCP | CEN/TR 14823 | ≤ 5ppm |
| THERMAL CONDUCTIVITY | EN 12667 / ISO 8302 | 0,11m ² k/w |
| BIOLOGICAL DURABILITY | EN 335 | Class 1 |
| BREAKING STRENGTH | EN 1533 | Pass |
| SLIPPERINESS | EN 15676 | Pass |
| MOISTURE CONTENT | EN 13183-1 | 7% (+/-2%) |

CERTIFICATION



EN 14342

