



Dimension plank

| | |
|------------------------|-------------------|
| LENGTH | 94-1/2" (2400 mm) |
| WIDTH | 8-3/4" (220 mm) |
| TOTAL THICKNESS | 5/8" (15 mm) |

Dimension box

| | |
|----------------------|-------------------|
| BOX LENGTH | 96-1/2" (2450 mm) |
| BOX WIDTH | 8-5/6" (225 mm) |
| BOX THICKNESS | 3-2/3" (90 mm) |
| BOX WEIGHT | 57 lb |
| LAYERS/BOX | 6 |
| SQFT/BOX | 34.12 sqft |

Dimension pallet

| | |
|----------------------|-------------------|
| PALLET LENGTH | 96-1/2" (2450 mm) |
| PALLET WIDTH | 45-1/3" (1150 mm) |
| PALLET HEIGHT | 34-2/3" (880 mm) |
| PALLET WEIGHT | 2320 lb |
| BOX/PALLET | 40 |
| SQFT/PALLET | 1364.86 sqft |

FEATURES

Top layer

| | |
|--------------------------|------------------------------|
| WOOD TYPE | Oak |
| LATIN NAME | Quercus Robur |
| GRADE | CLASSIC |
| CONSTRUCTION | 3-layer |
| BEVEL | Micro bevel 4 sides (0.5 mm) |
| SURFACE STRUCTURE | Brushed |

Composition of the support

| | |
|----------------------------|-----|
| SUPPORT TYPE | Fir |
| BASE OF THE SUPPORT | Fir |

Placement

| SYSTEM | APPLICATIONS | UNDERFLOOR HEATING |
|-------------------|---|--------------------|
| Tongue and groove | <ul style="list-style-type: none"> · Light household use · Moderate commercial use · Normal commercial use · Normal household use · Intensive commercial use | Yes |
| | | RE-SANDABLE |
| | | Yes |

TECHNICAL SPECIFICATIONS

| | Norm | Result |
|-----------------------|---------------------|------------------------|
| REACTION TO FIRE | EN 13501-1 | Dfl-S1 |
| FORMALDEHYDE EMISSION | CARB PH2 | CARB PH2 |
| PCP | CEN/TR 14823 | ≤ 5ppm |
| THERMAL CONDUCTIVITY | EN 12667 / ISO 8302 | 0,11m ² k/w |
| BIOLOGICAL DURABILITY | EN 335 | Class 1 |
| BREAKING STRENGTH | EN 1533 | Pass |
| SLIPPERINESS | EN 15676 | Pass |
| MOISTURE CONTENT | EN 13183-1 | 7% (+/-2%) |

CERTIFICATION



EN 14342

