14 MM PRIME - SUPER TUSCAN
A16845



Dimension plank

LENGTH	86 1/2″ RL (2200 mm RL)
WIDTH	7″ (180 mm)
TOTAL THICKNESS	9/16″ (14 mm)

Dimension box

BOX LENGTH	87″ (2210 mm)
BOX WIDTH	7 1/2″ (190 mm)
BOX THICKNESS	3 2/6″ (85 mm)
BOX WEIGHT	40 lb
LAGEN/PAK	6
SQFT/BOX	25.62 sqft

Dimension pallet

PALLET LENGTH	87 4/5″ (2230 mm)
PALLET WIDTH	47 1/4″ (1200 mm)
PALLET HEIGHT	43 2/3″ (1100 mm)
GEWICHT PALLET	2414 lb
BOX/PALLET	60
SQFT/PALLET	1537.20 sqft

FEATURES

Top layer

HOUTSOORT	Oak
LATIJNSE NAAM	Quercus Robur
SORTERING	PRIME
OPBOUW	2-layer
VELLING	Micro bevel 4 sides (0.5 mm)
OPPERVLAKTESTRUCTUUR	Smooth

Composition of the support

SUPPORT TYPE	Engineered
BASE OF THE SUPPORT	Plywood
TOTALE DIKTE DRAGER	11 mm

Placement

SYSTEM

Tongue and groove

APPLICATIONS

- Light household use
- Moderate commercial use
- Normal commercial use
- Normal household use
- Intensive commercial use

VLOERVERWARMING

Yes

HERSCHUURBAAR

Yes

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.

14 MM PRIME - SUPER TUSCAN
A16845

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	CARB PH2	CARB PH2
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION

EN 14342

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.