



Dimension plank

LENGTH	86 1/2" RL (2200 mm RL)
WIDTH	7" (180 mm)
TOTAL THICKNESS	9/16" (14 mm)

Dimension box

BOX LENGTH	87" (2210 mm)
BOX WIDTH	7 1/2" (190 mm)
BOX THICKNESS	3 2/6" (85 mm)
BOX WEIGHT	40 lb
LAYERS/BOX	6
SQFT/BOX	25.62 sqft

Dimension pallet

PALLET LENGTH	87 4/5" (2230 mm)
PALLET WIDTH	47 1/4" (1200 mm)
PALLET HEIGHT	43 2/3" (1100 mm)
PALLET WEIGHT	2414 lb
BOX/PALLET	60
SQFT/PALLET	1537.20 sqft

FEATURES

Top layer

WOOD TYPE	Oak
LATIN NAME	Quercus Robur
GRADE	ABCD
CONSTRUCTION	2-layer
BEVEL	Micro bevel 2 long sides (0,5 mm)
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Engineered
BASE OF THE SUPPORT	Plywood
TOTAL BEARER THICKNESS	11 mm

Placement

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	<ul style="list-style-type: none">· Light household use· Moderate commercial use· Normal commercial use· Normal household use· Intensive commercial use	Yes
		RE-SANDABLE
		Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	CARB PH2	CARB PH2
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

