



Dimension plank

LENGTH	92 1/2" (2350 mm RL)
WIDTH	9 1/2" (242 mm)
TOTAL THICKNESS	5/8" (15 mm)

Dimension box

BOX LENGTH	93" (2362 mm)
BOX WIDTH	9 3/4" (248 mm)
BOX THICKNESS	2 1/2" (64 mm)
BOX WEIGHT	45 lb
LAYERS/BOX	4
SQFT/BOX	24.48 sqft

Dimension pallet

PALLET LENGTH	93 2/3" (2380 mm)
PALLET WIDTH	38 1/2" (980 mm)
PALLET HEIGHT	41 1/2" (1055 mm)
PALLET WEIGHT	3375 lb
BOX/PALLET	75
SQFT/PALLET	1836.00 sqft

FEATURES

Top layer

WOOD TYPE	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC
CONSTRUCTION	2-layer
BEVEL	Micro bevel 2 long sides (0,5 mm)
SURFACE STRUCTURE	Brushed

Composition of the support

SUPPORT TYPE	Engineered
BASE OF THE SUPPORT	Plywood

Placement

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	<ul style="list-style-type: none"> Light household use 	Yes
	<ul style="list-style-type: none"> Moderate commercial use 	RE-SANDABLE
	<ul style="list-style-type: none"> Normal commercial use 	Yes
	<ul style="list-style-type: none"> Normal household use 	
	<ul style="list-style-type: none"> Intensive commercial use 	

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	CARB PH2	CARB PH2
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

