

15 MM CLASSIC - LAZIO A210354



C ·				
I)ım	ension	n	lan	k

LENGTH	92 1/2" (2350 mm RL)
WIDTH	7 1/2" (192 mm)
TOTAL THICKNESS	5/8" (15 mm)

Dimension box	
BOX LENGTH	93" (2362 mm)
BOX WIDTH	7 2/3" (195 mm)
BOX THICKNESS	2 1/2" (64 mm)
BOX WEIGHT	45 lb
LAYERS/BOX	4

SQFT/BOX

Dimension pallet	
PALLET LENGTH	93 2/3" (2380 mm)
PALLET WIDTH	38 1/2" (980 mm)
PALLET HEIGHT	41 1/2" (1055 mm)
PALLET WEIGHT	3375 lb
BOX/PALLET	75
SQFT/PALLET	1456.50 sqft

FEATURES

_			
10	р	la١	/ei

WOOD TYPE	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC
CONSTRUCTION	2-layer
BEVEL	Micro bevel 2 long sides (0,5 mm)

Composition of the support

19.42 sqft

SUPPORT TYPE	Engineered
BASE OF THE SUPPORT	Plywood

Placement

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	· Light household use	Yes
	· Moderate commercial use	RE-SANDABLE
		Yes
	· Normal commercial use	
	· Normal household use	
	· Intensive commercial use	

[©] This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables, graphs should in no way be distributed, used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables, graphs used in this sheet are intended only as illustrations. No rights can be derived from them.



15 MM CLASSIC - LAZIO A210354

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	CARB PH2	CARB PH2
PCP	CEN/TR 14823	≤5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION









